


A

B


C

D

E



E1 CEILING PLAN
SCALE: 3/32" = 1'-0"



SHEET NOTES

NEW LIGHTING FIXTURES KEY:

- A** LED FLAT HIGH BAY, 12x24 SUSPENDED (PROVIDE WHITE CORD)
- B** LED RECESSED DOWNLIGHT
- C** LED TRACK LIGHT, SUSPENDED, PROVIDE WATTAGE LIMITER (12'-0" A.F.F.)
- D** LED PENDANT AT WESTERN WEAR
- E** LED PENDANT AT PAINT AREA OVER TABLES
- F** LED 2x4 PANEL FIXTURE (LIGHT BAR (OFC))
- G** LED COMPASS HIGH BAY PENDANT WITH ACRYLIC REFLECTOR (90362) AND LENS (90363)
- H** LED TUBE 4' WITH TYPE C DRIVER FOR 1/2" 13W/T8 TUBES
- J** LED LIGHT STRIPS: TAPE TO UNDERSIDE OF GONDOLA SHELVES
- K** LED SCONE IN DRESSING ROOM
- L** EXTERIOR LED LIGHT FIXTURES
- M** EXTERIOR LED LIGHT FIXTURES

CEILING PLAN NOTES:

1. COORDINATE LIGHT FIXTURE LAYOUT WITH TENANTS FINAL FIXTURE PLAN
2. ALL INTERIOR SUSPENDED AND GYP. BOARD CEILING ARE TO BE 8'-0" A.F.F.
3. PAINT ENTIRE ROOF STRUCTURE, METAL DECK, BEAMS, TRUSSES, CONDUIT, DUCTWORK, ETC. IN SALES FLOOR AREA P-3 (DRY-FALL PATRIOT WHITE)
4. DO NOT ATTACH HANGER WIRE TO BOTTOM CHORD OF TRUSSES
5. TRACK LIGHTS IN CLOTHING PAD TO BE ATTACHED TO UN-STRUT MEMBERS, SUSPENDED FROM THE BOTTOM OF ROOF DECK, TRACK LIGHTS MUST BE STRAIGHT (IN-LINE) AND LEVEL
6. COORDINATE INSTALLATION OF LIGHT FIXTURES WITH DUCTWORK, TRAPEZE UNDER DUCTWORK WITH UN-STRUT WHERE REQUIRED TO KEEP LIGHT FIXTURES IN LINE

KEY NOTES

- 1 SUSPENDED GYP. BD. CEILING
- 2 EXPOSED TO STRUCTURE - PAINT ALL EXPOSED ROOF FRAMING MEMBERS AND DUCTWORK
- 3 BOTTOM OF ALL TYPE 'A' AND TOP OF TYPE 'H' LIGHTS IN SALES AREA TO BE SUSPENDED AT 14'-0" AFF. SEE E6/201
- 4 BOTTOM OF ALL TYPE 'A' LIGHTS IN WAREHOUSE TO BE AT 16'-0" AFF
- 5 PULL DOWN POWER CORD REELS, BOTTOM OF CORD TO BE SUSPENDED 12'-0" AFF
- 6 24" X 24" LOCKABLE ACCESS HATCH (TYP)
- 7 EXTERIOR SUSPENDED GYP. BD. CEILING (USG, CERTAINTED, FABCO OR EQUAL)
- 8 CONTINUOUS PERFORATED VINYL SOFFIT VENT
- 9 24" X 24" NON-LOCKABLE ACCESS HATCH (TYP)
- 10 DAYLIGHT OVERFLOW DRAIN 1" BELOW SOFFIT
- 11 BOTTOM OF HALO TO BE MOUNTED AT 9'-0" AFF, BOTTOM OF PENDANT FIXTURES TO BE MOUNTED AT 1'-6" AFF
- 12 METAL FLASHING AROUND EDGES OF CEILING IN AND AROUND VESTIBULE
- 13 BOTTOM OF FIXTURE @ 14'-0" AFF

NOVAK
ARCHITECTURE INC.

8380 SW NYBERG ST.
SUITE B
TUALATIN, OR 97062
P 503.352.4987
www.novakarchitecture.com

08/18/2023 3:32:22 PM
Permit Number: 25-01679-01
Eugene

Reviewed for Code Compliance

WILCO EUGENE
WILTH & WILLOW CREEK
EUGENE, OREGON 97402

WILCO
200 INDUSTRIAL WAY
MT. ANGEL, OR 97362

project number 18-25
date 10/03/22

revisions
1 06/02/23 AGENCY/QC REVIEW
2 07/06/23 TENANT

REGISTERED ARCHITECT
4140
TERRY J. NOVAK
PORTLAND, OREGON
STATE OF OREGON

07/22/2023 4:10:51 PM
A204 OVERALL CEILING PLAN

OVERALL
CEILING PLAN

sheet number

A204